



LUBRIN MULTI POWER

HD 15W-40

LUBRIN MULTI POWER HD 15W-40 is a semi-synthetic heavy duty diesel engine oil providing excellent control of piston cleanliness, wear, soot handling and lubricant stability.

Due to using combination of selective Base oil Group II/III and special additives with the most advanced technology. LUBRIN MULTI POWER HD 15W-40 is recommended for highly rated diesel engines meeting Euro I, Euro II, Euro III, Euro IV and Euro V emission requirements and running under very severe conditions, e.g. significantly extended oil drain intervals according to the manufacturer's recommendations. It is suitable for turbo-charging engines without particulate filters, and for some EGR engines and some engines fitted with SCR NOx reduction systems.

Performance Features:

- Excellent Thermal and oxidation stability
- Lower fuel and oil consumption
- Excellent wear control and deposit build-up
- Easy start-up

Performance Levels:

- API CI-4
- ACEA E7-08
- VOLVO VDS-4
- MAN 3277
- MB 228.5

Art No.: G0010

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

File No. M17613_2014.08.25
Name: LUBRIN MULTI POWER HD 15W-40
Page 1 of 2



Typical characteristics			
Data	Unit	Method	Value
Density at 15°C	kg/L	D 1298	0,875
Viscosity at 100°C	mm ² /s	D 445	16,20
Viscosity index (VI)		D 2270	141
Flash point (COC)	°C	D 93	218
Pour point	°C	D 97	-28
TBN	mgKOH/g	D 2896	12
The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change.			

Art No.: G0010

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

File No. M17613_2014.08.25
Name: LUBRIN MULTI POWER HD 15W-40
Page 2 of 2