



## LUBRIN® SUPERTEC SAE 5W-20

This is a fuel economy engine oil specially developed to meet the requirements of the latest Ford Ecoboost gasoline engines. It is developed using the most recent additive technology in combination with specially selected base oils with a high natural viscosity index.

### Recommended For:

API SN

ACEA A1/B1

Ford WSS-M2C-948-B

Typical characteristics			
Data	Unit	Method	Value
Density at 15°C	kg/L	ASTM D 4052	0.851
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 445	42.60
Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D 445	7.85
Viscosity Index (VI)		ASTM D 2270	156
Flash point (COC)	°C	ASTM D 92	215
Pour point	°C	ASTM D 6892	-35

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art No.: 66016

Lubrin GmbH  
Lübecker Str. 7, 65760 Eschborn, Germany  
Tel: +49 6196-202 9550  
Website: [www.lubrin.co](http://www.lubrin.co)  
Email: [info@lubrin.co](mailto:info@lubrin.co)

File No. M17616\_2015.03.12  
Name: MULTI POWER HD 15W-40  
Page 1 of 1