

LUBRIN® ECO FE LL4 SAE 0W-20

A fuel economy motor oil, developed according the most recent technology, based on specially selected base oils and a well balanced choice of advanced additives to obtain the following properties:

- lower fuel consumption
- reduced formation of combustion residues (mid SAPS)
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Recommended For:

VW 508 00/509 00

Art No.: 66027



Typical characteristics			
Data	Unit	Method	Value
Density at 15°C	kg/L	ASTM D 4052	0.832
Viscosity at 40°C	mm²/s	ASTM D 445	39.30
Viscosity at 100°C	mm²/s	ASTM D 445	7.93
Viscosity Index (VI)		ASTM D 2270	178
Flash point (COC)	°C	ASTM D 92	200
Pour point	°C	ASTM D 6892	-52

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art No.: 66027

Lubrin GmbH

Lüebecker Str. 7, 65760 Eschborn, Germany

Tel: +49 6196-202 9550 Website: <u>www.lubrin.co</u> Email: <u>info@lubrin.co</u> File No. M17627_2015.08.25 Name: ECO FE LL4 SAE 0W20

Page 2 of 2