



## LUBRIN® HLP ISO-VG 10

LUBRIN HLP ISO-VG 10 is a mineral oil based hydraulic fluid with effective additives. The reason for this hydraulic oils are Solventrefined products, used exclusively in the production of the refinery, the additive is specially designed for these base oils.

LUBRIN HLP ISO-VG 10 offers the best possible wear and corrosion protection even at the highest mechanical stresses. The oxidation inhibitors operate at maximum aging stability and allow longer oil drain intervals and thus lower maintenance. Hydraulic oils are used in all hydraulic systems. They have proven themselves in practice in countless systems and hydraulic systems. In thermally highly stressed hydraulic systems with high pressure pumps of all types, in sensitive control systems and also for the supply of small gears and for use in circulating systems.

### Recommended for:

ISO-VG 10

DIN 51 524 / part 2 (HLP)

Typical characteristics			
Data	Unit	Method	Value
Density at 15°C	Kg/L	D-4052	0,850
Viscosity at 40°C	mm <sup>2</sup> /s	D 445	38
Viscosity at 100°C	mm <sup>2</sup> /s	D 445	4,5
Viscosity index (VI)		D 2270	100
Flash point (COC)	°C	D 92	160
Pour point	°C	D 97	-5
TAN	mgKOH/g	D 2896	NIL_INERT

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art. No: 44001

Lubrin GmbH  
Lübecker Str. 7, 65760 Eschborn, Germany  
Tel: +49 6196-202 9550  
Website: [www.lubrin.co](http://www.lubrin.co)  
Email: [info@lubrin.co](mailto:info@lubrin.co)

File No. M17401\_2014.06.30  
Name: HLP ISO-VG 10

Page 1 of 1