



LUBRIN® COMPRESSOR OIL PS 46

COMPRESSOR OIL PS is a synthetic air compressor lubricant formulated of special PAO base fluids and mixed with high quality additives technology. It can give top performance oil-flooded air compressors of screw or vane design to provide long oil life and effective lubrication in severe applications.

Recommended for:

DIN 51 506-VDL

Typical characteristics			
Data	Unit	Method	Value
Density at 15°C	Kg/L	D-4052	0,843
Viscosity at 40°C	mm ² /s	D 445	46
Viscosity at 100°C	mm ² /s	D 445	7,9
Viscosity index (VI)		D 2270	142
Flash point (COC)	°C	D 92	242
Pour point	°C	D 97	-50

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art. No: 44025

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

File No. M17425_2015.01.29
Name: COMPRESSOR OIL PS 46
Page 1 of 1