



## LUBRIN® TURBINE OIL 100

A universal oil for turbines from specially selected refined base oils with good viscosity index. This turbine oil is for lubricating oil circulating systems of the modern steam and gas turbines, where usually high oil temperatures.

The turbine oil in addition to the usual additives so-called "metal deactivators" included to ensure the following properties:

- Good oxidation stability also at high temperatures
- Good protection against corrosion
- Good water separation
- Good air release
- Stable viscosity index

### Recommended for:

BS 489

DIN 51 515 (L-TD)

ISO 6743/0 T

Art. No: 44055

Lubrin GmbH  
Lübecker Str. 7, 65760 Eschborn, Germany  
Tel: +49 6196-202 9550  
Website: [www.lubrin.co](http://www.lubrin.co)  
Email: [info@lubrin.co](mailto:info@lubrin.co)

**File No. M17455\_2015.01.29**  
**Name: TURBINE OIL 100**  
**Page 1 of 2**



<b>Typical characteristics</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>Value</b>
Density at 15°C	Kg/L	DIN 51 757	0,885
Viscosity at 40°C	mm <sup>2</sup> /s	DIN 51 562	100
Viscosity at 100°C	mm <sup>2</sup> /s	DIN 51 562	11
Viscosity Index (VI)		ASTM ISO 2909	97
Flash point (COC)	°C	DIN ISO 2592	240
Pour point	°C	DIN ISO 3016	-10

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art. No: 44055

Lubrin GmbH  
Lübecker Str. 7, 65760 Eschborn, Germany  
Tel: +49 6196-202 9550  
Website: [www.lubrin.co](http://www.lubrin.co)  
Email: [info@lubrin.co](mailto:info@lubrin.co)

**File No. M17455\_2015.01.29**  
**Name: TURBINE OIL 100**  
**Page 2 of 2**