

LUBRIN® WATER SOLUBLE OIL

WATER SOLUBLE OIL is a Mineral based oil and high quality additives appropriate for Ferrous and non-ferrous metal machinery operations. It's a top stable oil-in-water emulsion developed for use as a metalworking fluid.

Performance Features:

- Emulsion Forming and Stability
- Corrosion inhibition on machines and components
- Anti-Foam specifications.

Recommended for:

DIN 51 517 / part 3

DIN 51 524 / part 2

Typical characteristics			
Data	Unit	Method	Value
Density at 15°C	kg/L	ASTM D 4052	0,900
Color			Dense White
pH at 5% Concentration	°C	ASTM D 1287	9,00
Corrosion Breakpoint (IP 287)	°C	IP 287	20,1

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art. No: 44058

Lubrin GmbH
 Lübecker Str. 7, 65760 Eschborn, Germany
 Tel: +49 6196-202 9550
 Website: www.lubrin.co
 Email: info@lubrin.co

File No. M17458_2015.01.29
 Name: WATER SOLUBLE OIL
 Page 1 of 2