



## **LUBRIN® Slideway and Track Lubrication Oil**

### **CGLP ISO-VG 68**

CGLP characterized by special lubricating and sliding properties and high adhesion. Therefore, it is particularly suitable for the lubrication of slide and bed ways. CGLP is also equipped with good corrosion protection properties to prevent rust and stain formation on slide and guiding ways. CGLP is largely resistant to aqueous metalworking fluids such as drilling, cutting and grinding emulsions or solutions. The sliding film is not washed off or swept away by these media. It is suitable for all types of lubrication such as pressure, circulation and central lubrication, also for the splash and pressure run lubrication and for lubrication by oil can by hand. It is also suitable for bearing and gear lubrication. For machines with a common oil circuit for the hydraulic and lubrication of the guiding ways, but at normal working temperatures.

#### **Performance Features:**

- High adhesion.
- Good corrosion protection properties.
- No rust and stain formation.
- Resistant to aqueous metalworking fluids.

#### **Recommended for:**

CGLP according to DIN 51 502

Art. No: 44060

<p>Lubrin GmbH Lübecker Str. 7, 65760 Eschborn, Germany Tel: +49 6196-202 9550 Website: <a href="http://www.lubrin.co">www.lubrin.co</a> Email: <a href="mailto:info@lubrin.co">info@lubrin.co</a></p>	<p><b>File No. M17460_2015.01.29</b> <b>Name: Slideway and Track Lubrication Oil</b> <b>CGLP ISO-VG 68</b></p> <p><b>Page 1 of 2</b></p>
--	--

<b>Typical characteristics</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>Value</b>
<b>Density at 15°C</b>	kg/L	DIN 51 757	0,883
<b>Viscosity at 40°C</b>	mm <sup>2</sup> /s	DIN 51 562	68
<b>Viscosity at 100°C</b>	mm <sup>2</sup> /s	DIN 51 562	9,00
<b>Viscosity Index (VI)</b>		DIN ISO 2909	109
<b>Flash point (COC)</b>	°C	DIN ISO 2592	225
<b>Pour point</b>	°C	DIN ISO 3016	-12

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art. No: 44060

Lubrin GmbH  
Lübecker Str. 7, 65760 Eschborn, Germany  
Tel: +49 6196-202 9550  
Website: [www.lubrin.co](http://www.lubrin.co)  
Email: [info@lubrin.co](mailto:info@lubrin.co)

**File No. M17460\_2015.01.29**  
**Name: Slideway and Track Lubrication Oil**  
**CGLP ISO-VG 68**

**Page 2 of 2**