



## LUBRIN® Hydraulic HVLP ISO-VG 68

HVLP 68 is a multigrade hydraulic oil with very good viscosity-temperature behaviour and cold flow properties. It was developed for hydraulic systems working outside and exposed to changing ambient temperatures. Combined with oxidation and corrosion inhibitors, modern base oils guarantee excellent oxidation stability and corrosion protection. EP additives minimize wear. Seals and hoses are not attacked.

### Recommended for:

DIN 51 524 / Teil 3

Bosch Rexroth

SEB 181222

AFNOR NF E 48-603 (HM, HV)

SIS SS 155434

Denison Filterability TP 02100

Hoesch HWN 2333

U.S Steel 126 u. 127

CETOP RP 91 H (HM, HV)

Sperry Vickers M-2950-S u. I-286-S

FZG-Test A 8,3/90 12

Art. No: 44071

Lubrin GmbH  
Lübecker Str. 7, 65760 Eschborn, Germany  
Tel: +49 6196-202 9550  
Website: [www.lubrin.co](http://www.lubrin.co)  
Email: [info@lubrin.co](mailto:info@lubrin.co)

**File No. M17471\_2015.01.29**  
**Name: Hydraulic HVLP ISO-VG 68**  
**Page 1 of 2**

| Typical characteristics |                    |                  |       |
|-------------------------|--------------------|------------------|-------|
| Data                    | Unit               | Method           | Value |
| Density at 15°C         | Kg/L               | DIN EN ISO 12185 | 0,870 |
| Viscosity at 40°C       | mm <sup>2</sup> /s | DIN 51 562-1     | 68,0  |
| Viscosity at 100°C      | mm <sup>2</sup> /s | DIN 51 562-1     | 10,9  |
| Viscosity Index (VI)    |                    | DIN ISO 2909     | 151   |
| Flash point (COC)       | °C                 | DIN ISO 2592     | 230   |
| Pour point              | °C                 | DIN ISO 3016     | -39   |

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art. No: 44071

Lubrin GmbH  
 Lünebecker Str. 7, 65760 Eschborn, Germany  
 Tel: +49 6196-202 9550  
 Website: [www.lubrin.co](http://www.lubrin.co)  
 Email: [info@lubrin.co](mailto:info@lubrin.co)

**File No. M17471\_2015.01.29**  
**Name: Hydraulic HVLP ISO-VG 68**  
**Page 2 of 2**