

LUBRIN® CALCIUM BASE 3 GREASE

LUBRIN CALCIUM BASE 3 GREASE is a Calcium thickened Grease with very highly adhesive properties.

APPLICATION :

- Vehicle chassis parts
- All metal joints, Hinges, Locks, Chains
- Bearings, guides and universal joints

PERFORMANCE FEATURES :

- Good water washout resistance
- Pumpable Features
- Working temperature in the rang -20°C to 60°C

PERFORMANCE LEVELS :

- DIN 51502

Art.No.: 22002

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: Calcium Base 3 Grease
2014.11.06

Page 1 of 2

Typical characteristics		
Properties	Method	Value
Soap type	ASTM D-3340	Calcium
NLGI Grade		3
Worked Cone Penetration	ASTM D-217	220-250
Color	Visual	Dark Brown
Dropping point	ASTM D-2265	95
Operative temperature		-20°C to +60°C
Classification: DIN 51502 : K3C-20		

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 22002

Lubrin GmbH Lünebecker Str. 7, 65760 Eschborn, Germany Tel: +49 6196-202 9550 Website: www.lubrin.co Email: info@lubrin.co	Name: Calcium Base 3 Grease 2014.11.06 Page 2 of 2
---	--