

LUBRIN® ALUMINIUM COMPLEX GREASE

LUBRIN ALUMINIUM COMPLEX GREASE is a kind of multifunction Grease blended of paraffinic base oil and Aluminum complex thickener.

LUBRIN ALUMINIUM COMPLEX GREASE contains additives with EP properties as well as Anti-wear and Anti-corrosion properties and suitable for central lubrication system for which has good pumpability. It is been using extensively in metallurgy area.

APPLICATION :

- Open Gears Running-in
- Used tooth flanks surfaces
- Rotary Kilns and dryers

PERFORMANCE FEATURES :

- High dropping point
- Good colloidal and shear stability
- Water resistance property
- Anti-corrosion and anti-wear property
- Extreme pressure properties

PERFORMANCE LEVELS :

- DIN 51502

Art.No.: 22006

Typical characteristics		
Properties	Method	Value
Soap type	ASTM D-3340	Aluminium Complex
NLGI Grade		0/00
Viscosity at 40°C	ASTM D-445	600 mm ² /s
Color	Visual	Black
Dropping point	ASTM D-2265	220
Operative temperature		-20°C to +150°C
Classification: DIN 51502 : OGP0N-20 , OGP00N-20		

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 22006

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: ALUMINIUM COMPLEX GREASE
2014.11.06

Page 2 of 2