

LUBRIN[®] LITHIUM BASE 2 GREASE

LUBRIN LITHIUM BASE 2 GREASE is a multi-purpose Grease made of mineral oil and lithium 12-hydroxystearate thickener with good stability, water resistance and softening resistance at high operating temperatures.

APPLICATION :

- Automotive Chassis
- Ball joints and universal joints
- Wheel bearings
- Loaded slide-ball and roller-bearings
- Universal joints
- Electric motors bearing
- Compressors and pumps

PERFORMANCE FEATURES :

- Working temperature from -20°C to 130°C
- Excellent thermal , Oxidation & mechanical stability
- High corrosion protection
- Long-life Greasing application
- Good water washout resistance

PERFORMANCE LEVELS :

- DIN 51502

Art.No.: 22007

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: Lithium Base 2 Grease
2014.11.06

Page 1 of 2



LUBRICANTS.ADDITIVES.CAR CARE

Typical characteristics		
Properties	Method	Value
Soap type	ASTM D-3340	Lithium
NLGI Grade		2
Worked Cone Penetration	ASTM D-217	260-295
Color	Visual	Cream
Dropping point	ASTM D-2265	185
Operative temperature		-20°C to +130°C
Classification: DIN 51502 : K2K-20		

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 22007

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: Lithium Base 2 Grease
2014.11.06

Page 2 of 2