

LUBRIN[®] LITHIUM COMPLEX BASE 2 GREASE

LUBRIN LITHIUM COMPLEX BASE 2 GREASE is a premium multi-purpose Grease based on high viscosity index mineral oil and a lithium complex soap thickener.

LUBRIN LITHIUM COMPLEX BASE 2 GREASE is high performance high temperature Grease for slow high loaded large bearings and contains latest additives to ensure excellent high temperature, anti-oxidant and anti-corrosion performance.

APPLICATION :

- High temperature wheel bearings (Disc Brakes)
- High loaded large bearings and rollers operating at high temperatures
- Roller & ball bearings
- Electric motor bearings
- Throw-out bearings, universal joints and chassis

PERFORMANCE FEATURES :

- High Dropping point
- High temperature performance
- Excellent anti-oxidant and anti-corrosion properties
- Excellent water resistance
- Mechanical stability even under vibrating conditions

PERFORMANCE LEVELS :

- DIN 51502

Art.No.: 22014

Typical characteristics		
Properties	Method	Value
Soap type	ASTM D-3340	Lithium Complex
NLGI Grade		2
Worked Cone Penetration	ASTM D-217	265-295
Color	Visual	Green
Dropping point	ASTM D-2265	265
Operative temperature		-20°C to +160°C
Classification: DIN 51502 : K2P-20		

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 22014

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: Lithium Complex Base 2 Grease
2014.11.06

Page 2 of 2