

LUBRIN® SUPER HD SAE 50

LUBRIN SUPER HD SAE 50 is a monograde Heavy duty Diesel engine oil. It has well performance additives to protect engine wear providing full lubrication and consistent performance and it's suitable for use in hydraulic clutches, transmissions, converter Gear transmissions and retarders as hydraulic oil where use of monograde oils is recommended by the equipment manufacturer.

APPLICATION :

- Mobile emergency sets
- Tugs and fishing vessels
- Agricultural aggregates
- Construction machinery
- Lawnmowers

PERFORMANCE FEATURES :

- Good detergency and dispersancy Properties
- Good oxidation and thermal stability
- Good anti-wear properties
- High viscosity index base oils

PERFORMANCE LEVELS :

- API CD / SF

Art.No.: 33006

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: SUPER HD SAE 50
2014.09.08

Page 1 of 2

Typical characteristics			
Properties	Unit	Method	Value
Density at 15°C	kg/L	ASTM D-1298	0,913
Viscosity at 100°C	mm ² /s	ASTM D-445	19,70
Viscosity index (VI)		ASTM D-2270	92
Flash point (COC)	°C	ASTM D-93	250
Pour point	°C	ASTM D-97	-12
TBN	mgKOH/g	ASTM D-2896	10,50

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 33006

Lubrin GmbH Lünebecker Str. 7, 65760 Eschborn, Germany Tel: +49 6196-202 9550 Website: www.lubrin.co Email: info@lubrin.co	Name: SUPER HD SAE 50 2014.09.08 Page 2 of 2
---	--