

LUBRIN[®] SUPER HDX SAE 20W-50

LUBRIN SUPER HDX SAE 20W-50 is premium multi-Grade high viscosity base oil to protect the engine systems of turbo-charged from dirt and sludge building-up and prolongs the engine life usefully.

APPLICATION :

- Gasoline vehicles with carburetor system
- Turbo-charges indirect injection diesel engines

PERFORMANCE FEATURES :

- Protection against dirt and sludge building-up
- Easy cold start-up
- Oil degradation resistance

PERFORMANCE LEVELS :

- API CD / SF
- MIL-L-2104D

Art.No.: 33010

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: SUPER HDX SAE 20W-50
2014.09.08

Page 1 of 2

Typical characteristics			
Properties	Unit	Method	Value
Density at 15°C	kg/L	ASTM D-1298	0,899
Viscosity at 100°C	mm ² /s	ASTM D-445	20
Viscosity index (VI)		ASTM D-2270	125
Flash point (COC)	°C	ASTM D-93	232
Pour point	°C	ASTM D-97	-24
TBN	mgKOH/g	ASTM D-2896	12

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 33010

Lubrin GmbH Lünebecker Str. 7, 65760 Eschborn, Germany Tel: +49 6196-202 9550 Website: www.lubrin.co Email: info@lubrin.co	Name: SUPER HDX SAE 20W-50 2014.09.08 Page 2 of 2
---	---