

## **LUBRIN<sup>®</sup> SUPER HDX SAE 30**

LUBRIN SUPER HDX SAE 30 is a monograde Heavy duty Diesel engine oil. It has well performance additives to protect engine wear providing full lubrication and consistent performance and it's suitable for use in non-turbocharged engines where use of monograde oils is recommended by the equipment manufacturer.

### **APPLICATION :**

- Hydraulic and transmissions
- Mobile Hydraulic systems

### **PERFORMANCE FEATURES :**

- Full system lubrication
- Good anti-wear properties
- High viscosity index base oils

### **PERFORMANCE LEVELS :**

- API CD / SF
- MIL-L-2104D

Art.No.: 33014

Lubrin GmbH  
Lübecker Str. 7, 65760 Eschborn, Germany  
Tel: +49 6196-202 9550  
Website: [www.lubrin.co](http://www.lubrin.co)  
Email: [info@lubrin.co](mailto:info@lubrin.co)

Name: SUPER HDX SAE 30  
2014.09.08

Page 1 of 2

Typical characteristics			
Properties	Unit	Method	Value
Density at 15°C	kg/L	ASTM D-1298	0,890
Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D-445	12
Viscosity index (VI)		ASTM D-2270	95
Flash point (COC)	°C	ASTM D-93	240
Pour point	°C	ASTM D-97	-18
TBN	mgKOH/g	ASTM D-2896	12

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 33014

Lubrin GmbH Lünebecker Str. 7, 65760 Eschborn, Germany Tel: +49 6196-202 9550 Website: <a href="http://www.lubrin.co">www.lubrin.co</a> Email: <a href="mailto:info@lubrin.co">info@lubrin.co</a>	Name: SUPER HDX SAE 30 2014.09.08  Page 2 of 2
---	---