

LUBRIN[®] GEAR OIL CLP ISO-VG 220

LUBRIN GEAR OIL CLP ISO-VG 220 is formulated industrial Gears working under extreme pressure conditions. It provides long life and extra protection and performance for Gears working efficiently by offering good corrosion protection and water separation.

APPLICATION :

- Industrial Gear systems
- Highly loaded Gear systems
- Bearings, Spiral and automotive hypoid Gears

PERFORMANCE FEATURES :

- Included Of EP performance features
- Long oil life and capability
- Extra Anti-friction and wear characteristics
- Excellent Load Carrying capacity
- Outstanding oxidation and thermal stability
- Maintaining system efficiency

PERFORMANCE LEVELS :

- DIN 51517 PART 3 (CLP), U.S STEEL 224
- ANSI / AGMA 9005 E02, DAVID BROWN S 1.53-101

Art.No.: 44042

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: GEAR OIL CLP ISO-VG 220
2014.06.24

Page 1 of 2

Typical characteristics			
Properties	Unit	Method	Value
Viscosity at 40°C	mm ² /s	ASTM D-445	220
Viscosity at 100°C	mm ² /s	ASTM D-445	19
Density at 15°C	Kg/L	ASTM D-4052	0,900
Viscosity index (VI)		ASTM D-2270	96
Flash point (COC)	°C	ASTM D-92	240
Pour point	°C	ASTM D-97	-18

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 44042

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: GEAR OIL CLP ISO-VG 220
2014.06.24

Page 2 of 2