

## LUBRIN® QUENCHING OIL HQ 145

LUBRIN QUENCHING OIL HQ 145 is recommended for cold quenching and should be used for hardening steels with alloy content.

### APPLICATION :

- Quenching of alloyed steels in cold quenching operations

### PERFORMANCE FEATURES :

- Low aromatic components
- Low viscosity

Typical characteristics			
Properties	Unit	Method	Value
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D-445	26
Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D-445	5
Density at 15°C	Kg/L	ASTM D-4052	0,852
Viscosity index (VI)		ASTM D-2270	119
Flash point (COC)	°C	ASTM D-92	202
Pour point	°C	ASTM D-97	-6

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 44064

Lubrin GmbH  
 Lünebecker Str. 7, 65760 Eschborn, Germany  
 Tel: +49 6196-202 9550  
 Website: [www.lubrin.co](http://www.lubrin.co)  
 Email: [info@lubrin.co](mailto:info@lubrin.co)

Name: QUENCHING OIL HQ 145  
 2014.03.14

Page 1 of 1