

LUBRIN[®] FLUSHING Oil

LUBRIN FLUSHING Oil Formulated from high quality mineral base stock for flushing engine or machinery in the engine oil draining process. After engine oil draining, fills the crankcase or sump with Flushing Oil and operates with the mild condition for 5-10 minutes, then completely drains the Flushing Oil and refills with fresh engine oil.

PERFORMANCE FEATURES :

- High detergent efficiency in removing deposits from engine system according to low viscosity characteristic
- For cleansing the general car engine systems
- For cleansing the industrial machinery

Typical characteristics			
Properties	Unit	Method	Value
Viscosity at 40°C	mm ² /s	ASTM D-445	32
Viscosity at 100°C	mm ² /s	ASTM D-445	5,50
Density at 15°C	Kg/L	ASTM D-4052	0,877
Viscosity index (VI)		ASTM D-2270	107
Flash point (COC)	°C	ASTM D-92	198
Pour point	°C	ASTM D-97	-18

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 44097

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: FLUSHING Oil
2014.03.14

Page 1 of 1