



LUBRIN® GEAR OIL EP SAE 80W

LUBRIN GEAR OIL EP SAE 80W is a Universal driveline lubricant and superior quality automotive Gear lubricant specially designed for use in Gearboxes and axles.

APPLICATION :

- Transmission and axles in tractors or heavy duty passenger vehicles
- Heavily loaded axles and non-synchronized transmission

PERFORMANCE FEATURES :

- Excellent protection wear and corrosion
- Least power loss and Gear efficiency
- Gear efficiency and higher fuel economy
- Longer oil drain capability
- Extreme-pressure properties

PERFORMANCE LEVELS :

- API GL-4
- MIL-L 2105

Art.No.: 55004

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: GEAR OIL EP SAE 80W
2014.06.24

Page 1 of 2

Typical characteristics			
Properties	Unit	Method	Value
Viscosity at 40°C	mm ² /s	ASTM D-445	85,60
Viscosity at 100°C	mm ² /s	ASTM D-445	9,70
Density at 15°C	Kg/L	ASTM D-4052	0,892
Viscosity index (VI)		ASTM D-2270	90
Flash point (COC)	°C	ASTM D-92	222
Pour point	°C	ASTM D-97	-30

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 55004

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: GEAR OIL EP SAE 80W
2014.06.24

Page 2 of 2