LUBRIN® GEAR OIL EP SAE 80W-90

LUBRIN GEAR OIL EP SAE 80W-90 is a Universal driveline lubricant and superior quality automotive Gear lubricant specially designed for use in Gearboxes and axles.

APPLICATION :

- Transmission and axles in tractors or heavy duty passenger vehicles
- Heavily loaded axles and non-synchronized transmission

PERFORMANCE FEATURES :

- Excellent protection wear and corrosion
- Least power loss and Gear efficiency
- Gear efficiency and higher fuel economy
- Longer oil drain capability
- Extreme-pressure properties

PERFORMANCE LEVELS :

- API GL-4
- MIL-L 2105

Art.No.: 55005

Typical characteristics			
Properties	**Unit**	**Method**	**Value**
Viscosity at 40°C	mm²/s	ASTM D-445	128,60
Viscosity at 100°C	mm²/s	ASTM D-445	15,20
Density at 15°C	Kg/L	ASTM D-4052	0,902
Viscosity index (VI)		ASTM D-2270	122
Flash point (COC)	°C	ASTM D-92	212
Pour point	°C	ASTM D-97	-30

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 55005