



## **LUBRIN® GEAR OIL EP SAE 85W-90**

LUBRIN GEAR OIL EP SAE 85W-90 is a Universal driveline lubricant and superior quality automotive Gear lubricant specially designed for use in Gearboxes and axles.

### **APPLICATION :**

- Transmission and axles in tractors or heavy duty passenger vehicles
- Heavily loaded axles and non-synchronized transmission

### **PERFORMANCE FEATURES :**

- Excellent protection wear and corrosion
- Least power loss and Gear efficiency
- Gear efficiency and higher fuel economy
- Longer oil drain capability
- Extreme-pressure properties

### **PERFORMANCE LEVELS :**

- API GL-4
- MIL-L 2105

Art.No.: 55006

Lubrin GmbH  
Lübecker Str. 7, 65760 Eschborn, Germany  
Tel: +49 6196-202 9550  
Website: [www.lubrin.co](http://www.lubrin.co)  
Email: [info@lubrin.co](mailto:info@lubrin.co)

Name: GEAR OIL EP SAE 85W-90  
2014.06.24

Page 1 of 2

Typical characteristics			
Properties	Unit	Method	Value
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D-445	203,20
Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D-445	16,70
Density at 15°C	Kg/L	ASTM D-4052	0,912
Viscosity index (VI)		ASTM D-2270	84
Flash point (COC)	°C	ASTM D-92	228
Pour point	°C	ASTM D-97	-18

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 55006

Lubrin GmbH  
Lübecker Str. 7, 65760 Eschborn, Germany  
Tel: +49 6196-202 9550  
Website: [www.lubrin.co](http://www.lubrin.co)  
Email: [info@lubrin.co](mailto:info@lubrin.co)

Name: GEAR OIL EP SAE 85W-90  
2014.06.24

Page 2 of 2