

LUBRIN[®] GEAR OIL EP-ML SAE 85W-140

LUBRIN GEAR OIL EP-ML SAE 85W-140 is especially suitable for lubrication of the drive train that lowers the operating temperature and ensures long term Gear and seal protection and longer oil life.

LUBRIN GEAR OIL EP-ML SAE 85W-140 is an excellent transmission and axle oil designed to provide ultimate protection to the latest heavy duty manual transmissions and axles.

APPLICATION :

- Transmission and axles
- Heavily loaded axles and non-synchronized transmission
- Drive trains

PERFORMANCE FEATURES :

- High viscosity index
- Excellent anti-corrosion, anti-foam, anti-rust and dispersivity properties
- Excellent resistance to oxidation and high shear stability
- Fuel-efficient, long life
- Gear efficiency and higher fuel economy
- Longer oil drain capability
- Extreme-pressure properties

PERFORMANCE LEVELS :

- API GL-5
- MIL-L 2105D
- MAN 342M2
- ZF TE-ML 05A, C & D

Art.No.: 55014

Typical characteristics			
Properties	Unit	Method	Value
Viscosity at 40°C	mm ² /s	ASTM D-445	344,80
Viscosity at 100°C	mm ² /s	ASTM D-445	25
Density at 15°C	Kg/L	ASTM D-4052	0,906
Viscosity index (VI)		ASTM D-2270	94
Flash point (COC)	°C	ASTM D-92	222
Pour point	°C	ASTM D-97	-15

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 55014

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: GEAR OIL EP-ML SAE 85W-140
2014.06.24

Page 2 of 2