

LUBRIN[®] EXTRA PLUS SAE 10W-40

LUBRIN EXTRA PLUS SAE 10W-40 is a high performance semi-synthetic oil to be used in gasoline and diesel engines of passenger car and light vans with or without Turbo-charger. This product is not suitable for diesel engines equipped with a Diesel Particle Filter (DPF).

PERFORMANCE FEATURES :

- Very good low temperature properties
- Protection to wear by cold start
- Very high thermal and oxidation stability
- Excellent resistance against foaming, corrosion and wear
- High dispersancy and detergency level

PERFORMANCE LEVELS :

- API SL / CF
- VW 501.01 / 505.00
- MB 229.1
- ACEA A3 / B4

Art.No.: 66002

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: EXTRA PLUS SAE 10W-40
2014.04.11

Page 1 of 2

Typical characteristics			
Properties	Unit	Method	Value
Density at 15°C	kg/L	ASTM D-1298	0,881
Viscosity at 100°C	mm ² /s	ASTM D-445	15,1
Viscosity index (VI)		ASTM D-2270	167
Flash point (COC)	°C	ASTM D-93	214
Pour point	°C	ASTM D-97	-33
TBN	mgKOH/g	ASTM D-2896	7,5

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 66002

Lubrin GmbH Lünebecker Str. 7, 65760 Eschborn, Germany Tel: +49 6196-202 9550 Website: www.lubrin.co Email: info@lubrin.co	Name: EXTRA PLUS SAE 10W-40 2014.04.11 Page 2 of 2
---	--