

LUBRIN[®] ULTRA TEC SAE 5W-40

LUBRIN ULTRA TEC SAE 5W-40 is synthetic motor oil formulated to provide exceptional wear protection in hot or cold operating temperatures and outstanding oxidation stability. It provides protection for extended oil drains, heavy loads and for vehicles requiring a synthetic motor oil.

LUBRIN ULTRA TEC SAE 5W-40 protects the engine over a wide range of extreme temperatures, particularly in super-hot operating areas such as the turbocharger and meets demanding European specifications.

PERFORMANCE FEATURES :

- Fast cold start
- High and very stable viscosity index
- High resistance against shearing
- Very strong resistance against oxidation
- Lowest engine deposit and emissions
- Outstanding wear protection

PERFORMANCE LEVELS :

- API SN / CF
- ACEA C3
- VW 505.00 / 505.01
- MB 229.51
- Renault RN0700
- BMW Longlife-04
- GM dexos 2 TM
- Porsche A40

Art.No.: 66004

Lubrin GmbH
Lübecker Str. 7, 65760 Eschborn, Germany
Tel: +49 6196-202 9550
Website: www.lubrin.co
Email: info@lubrin.co

Name: ULTRA TEC SAE 5W-40
2014.04.11

Page 1 of 2

Typical characteristics			
Properties	Unit	Method	Value
Density at 15°C	kg/L	ASTM D-1298	0,854
Viscosity at 100°C	mm ² /s	ASTM D-445	15,5
Viscosity index (VI)		ASTM D-2270	165
Flash point (COC)	°C	ASTM D-93	224
Pour point	°C	ASTM D-97	-42
TBN	mgKOH/g	ASTM D-2896	7,9

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guarantee of certain product properties or of the suitability of the product for a specific application. LUBRIN products are continually improved. Therefore LUBRIN reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms.

Art.No.: 66004

Lubrin GmbH Lünebecker Str. 7, 65760 Eschborn, Germany Tel: +49 6196-202 9550 Website: www.lubrin.co Email: info@lubrin.co	Name: ULTRA TEC SAE 5W-40 2014.04.11 Page 2 of 2
---	--